

# DHB-E 18/21/24 LCD Set

CONVENIENCE INSTANTANEOUS WATER  
HEATER

PRODUCT-NO.: 203866

## The main features

Pivoting appliance cover and programming unit for increased operating convenience on undersink installations

Precise temperature selection via rotary selector

Suitable for reheating preheated water up to 55 °C (maximum inlet temperature 70 °C)

LCD with temperature display

Electronic output control with 3i technology for maximum energy efficiency and accurate temperature delivery

Quick PROFI-RAPID installation

Selectable output 18/21/24 kW in a single appliance





Type	DHB-E 11/13 LCD	DHB-E 18/21/24 LCD Set	DHB-E 18/21/24 LCD
Part no.	236743	203866	236745
Rated output	11/13,5 kW	18/21/24 kW	18/21/24 kW
Width	225 mm	225 mm	225 mm
Height	466 mm	466 mm	466 mm
Depth	116 mm	116 mm	116 mm

## Technical data

Rated voltage	400 V	400 V	400 V
Phases	3/PE	3/PE	3/PE
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Rated current	17,5/19,5 A	29/31/35 A	29/31/35 A
Fuses	20 A	32/32/35 A	32/32/35 A
Temperature adjustment	Off, 20-60 °C	Off, 20-60 °C	Off, 20-60 °C
Specific conductivity $\sigma_{15} \leq$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$
Energy efficiency class	A	A	A
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight	2,8 kg	2,9 kg	2,9 kg



Type	DHB-E 27 LCD Set
Part no.	203865
Rated output	18/21/24 kW
Width	225 mm
Height	466 mm
Depth	116 mm

#### Technical data

Rated voltage	400 V
Phases	3/PE
Frequency	50/60 Hz
Rated current	29/31/35 A
Fuses	32/32/35 A
Temperature adjustment	Off, 20-60 °C
Specific conductivity $\sigma_{15} \leq$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$	900 $\Omega \text{ cm}$
Energy efficiency class	A
Colour	white
IP-Rating	IP25
Weight	2,9 kg

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.