

DCE-S 6/8 Plus

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 238153

Compact DCE-S Plus instantaneous water heater – For easy showering pleasure.

With its high efficiency and output, the DCE-S Plus offers a reliable and constant supply of hot water for several smaller draw-off points (hand washbasins) or one larger one (shower).

As efficient as it is compact.

The rotary selector quickly enables accurate temperature delivery between 20 and 60 °C. The temperature can be selected variably, either in °C or °F. The rotary selector makes operation extremely easy.



The main features

Electronically controlled compact instantaneous water heater with 3i technology

Very good energy efficiency thanks to electronic output control

Precise temperature selection from 20 °C to 60 °C

Permanently selectable temperature limit can be set to 43 °C, 50 °C or 55 °C

Suitable for showers

Good price/performance ratio



Type	DCE-S 6/8 Plus + 2 x WSH 20	DCE-S 10/12 Plus + 2 x WSH 20	DCE-S 6/8 Plus
Part no.	203849	203848	238153
Rated output			6,0/8,0 kW
Height			372 mm
Width			217 mm
Depth			109 mm

Technical data

Rated voltage 1	220 V
Rated output 1	6,0/8,0 kW
Rated current 1	27,3/36,4 A
Fuse 1	30/40 A
Frequency 1	50/60 Hz
Rated voltage 2	230 V
Rated output 2	6,6/8,7 kW
Rated current 2	28,5/38,0 A
Fuse 2	30/40 A
Frequency 2	50/60 Hz
Rated voltage 3	240 V
Rated output 3	7,2/9,6 kW
Rated current 3	30,0/40,0 A
Fuse 3	30/40 A
Frequency 3	50/60 Hz
Phases	1/N/PE
Temperature adjustment	20-60 °C

Specific resistance $\rho_{15} \geq$	1100 Ω cm
Specific conductivity $\sigma_{15} \leq$	910 $\mu\text{S}/\text{cm}$
Energy efficiency class	A
Colour	white
IP-Rating	IP25
Weight	2,5 kg



Type	DCE-S 10/12 Plus
Part no.	238154
Rated output	10,0/12,0 kW
Height	372 mm
Width	217 mm
Depth	109 mm

Technical data

Rated voltage 1	220 V
Rated output 1	10,0/12,0 kW
Rated current 1	45,5/54,5 A
Fuse 1	50/60 A
Frequency 1	50/60 Hz
Rated voltage 2	230 V
Rated output 2	11,0/13,1 kW
Rated current 2	47,8/57,0 A
Fuse 2	50/60 A
Frequency 2	50/60 Hz
Rated voltage 3	240 V
Rated output 3	12,0/14,3 kW
Rated current 3	50,0/59,5 A
Fuse 3	50/60 A
Frequency 3	50/60 Hz
Phases	1/N/PE
Temperature adjustment	20-60 °C
Specific resistance $\rho_{15} \geq$	1100 Ω cm

Specific conductivity $\sigma_{15 \leq}$	910 $\mu\text{S}/\text{cm}$
Energy efficiency class	A
Colour	white
IP-Rating	IP25
Weight	2,5 kg

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.