

# DHE 27 Set

CONVENIENCE INSTANTANEOUS WATER  
HEATER

PRODUCT-NO.: 204285

## The main features

Fully electronic output control with 4i technology for maximum energy efficiency and permanently accurate temperature delivery

Internal temperature limit can be adjusted to 55, 50 or 43 °C by the qualified contractor; temperature limit (childproofing) can be selected by the user

Pivoting appliance cover and programming unit for increased operating convenience on undersink installations

Maximum energy efficiency through selectable ECO mode

Display of consumption for optimum cost transparency

Two temperature memory buttons for quick temperature selection

Extensive range of convenience and safety functions

Large, backlit multifunction display for a quick overview and easy operation

Profi-Rapid - the innovative installation concept





Type	DHE 18/21/24 Set	DHE 27 Set
Part no.	204284	204285
Rated output	18/21/24 kW	27 kW
Width	225 mm	225 mm
Height	466 mm	466 mm
Depth	116 mm	116 mm

## Technical data

Rated voltage	400 V	400 V
Phases	3/PE	3/PE
Frequency	50/60 Hz	50/- Hz
Rated current	29/31/35 A	39 A
Fuses	32/32/35 A	40 A
Temperature adjustment	Off, 20-60 °C	Off, 20-60 °C
Specific conductivity $\sigma_{15} \leq$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$
Energy efficiency class	A	A
Colour	white	white
IP-Rating	IP25	IP25
Weight	3,1 kg	3,1 kg

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.